

| Properties | | | |
|--------------------|---------------------------------|--|--|
| Connection 1 - 3 | metric cylindrical outer thread | | |
| Sealing form 1 - 3 | Butt construction | | |
| Design | for bulkhead mounting | | |
| Construction | T shaped | | |
| Material | Steel | | |
| Surface | electro galvanised | | |



| Item | | | | | | | |
|----------------|------------|------------|------------|------|------|------|------|
| Identification | G1 | G2 | G3 | i | L1 | L2 | AF |
| | | | | (mm) | (mm) | (mm) | (mm) |
| K 440-26 | M 22 x 1.5 | M 22 x 1.5 | M 22 x 1.5 | 34 | 70 | 54 | 19 |

AF = Width across flats

| Product versions | | | | |
|------------------|---|--|--|--|
| K 44-32 / K44-61 | Connecting fitting, T shaped, with union nut, cutting ring, pressure ring, sealing ring and counter nut | | | |
| K 44-46 | Connecting fitting, T shaped, with union nut, cutting ring, pressure ring and sealing ring. | | | |
| K 47-21 | Connecting fitting, T shaped, with union nut, cutting ring, pressure ring, sealing ring, counter nut and hose fitting | | | |
| K 47-22 | Connecting fitting, T shaped, with union nut, cutting ring, pressure ring, sealing ring, counter nut and hose fitting | | | |