

# K 440-28 - K 440-47

Connection socket, T shaped

## Properties

<b>Connection 1</b>	metric cylindrical outer thread
<b>Sealing form 1</b>	24° inner cone
<b>Connection 2 + 3</b>	metric cylindrical outer thread
<b>Sealing form 2 + 3</b>	Butt construction
<b>Construction</b>	T shaped
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Item

Identification	Ø d2 (mm)	G1	G2	G3	i1 (mm)	i2 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	AF (mm)
<b>K 440-28</b>	10	M 16 x 1.5	M 22 x 1.5	M 22 x 1.5	12	25	20	25	33	27
<b>K 440-35</b>	6	M 12 x 1.5	M 22 x 1.5	M 22 x 1.5	12	25	20	25	33	27
<b>K 440-47</b>	6	M 12 x 1.5	M 22 x 1.5	M 26 x 1.5	15	25	23	25	33	27

AF = Width across flats

## Product versions

<b>K 44-35 - K 44-66</b>	Reducing connecting fitting, T shaped, with union nut, cutting ring, pressure ring, sealing ring and counter nut
<b>K 44-38 / K 44-82</b>	Connecting fitting, T shaped, with union nut, cutting ring and counter nut
<b>K 44-48</b>	Reducing connecting fitting, T shaped, with union nut, cutting ring, pressure ring and sealing ring.
<b>K 46-12-5 / K 46-12-9</b>	Connecting fitting, T shaped with test connection, with union nut, cutting ring, pressure ring, sealing ring and test connection
<b>K 47-20</b>	Connecting fitting, T shaped, Steel