

Properties

Connection 1	metric cylindrical outer thread
Sealing form 1	24° inner cone
Connection 2 + 3	metric cylindrical outer thread
Sealing form 2 + 3	Butt construction
Construction	T shaped
Material	Steel
Surface	electro galvanised



Item

Identification	Ø d2 (mm)	G1	G2	G3	i1 (mm)	i2 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	AF (mm)
K 440-28	10	M 16 x 1.5	M 22 x 1.5	M 22 x 1.5	12	25	20	25	33	27
K 440-35	6	M 12 x 1.5	M 22 x 1.5	M 22 x 1.5	12	25	20	25	33	27
K 440-47	6	M 12 x 1.5	M 22 x 1.5	M 26 x 1.5	15	25	23	25	33	27

AF = Width across flats

Product versions

K 44-35 - K 44-66	Reducing connecting fitting, T shaped, with union nut, cutting ring, pressure ring, sealing ring and counter nut
K 44-38 / K 44-82	Connecting fitting, T shaped, with union nut, cutting ring and counter nut
K 44-48	Reducing connecting fitting, T shaped, with union nut, cutting ring, pressure ring and sealing ring.
K 46-12-5 / K 46-12-9	Connecting fitting, T shaped with test connection, with union nut, cutting ring, pressure ring, sealing ring and test connection
K 47-20	Connecting fitting, T shaped, Steel