

K 440-28 - K 440-47

Connection socket, T shaped

Properties

| | |
|---------------------------|---------------------------------|
| Connection 1 | metric cylindrical outer thread |
| Sealing form 1 | 24° inner cone |
| Connection 2 + 3 | metric cylindrical outer thread |
| Sealing form 2 + 3 | Butt construction |
| Construction | T shaped |
| Material | Steel |
| Surface | electro galvanised |



Item

| Identification | Ø d2 (mm) | G1 | G2 | G3 | i1 (mm) | i2 (mm) | L1 (mm) | L2 (mm) | L3 (mm) | AF (mm) |
|-----------------|--------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|
| K 440-28 | 10 | M 16 x 1.5 | M 22 x 1.5 | M 22 x 1.5 | 12 | 25 | 20 | 25 | 33 | 27 |
| K 440-35 | 6 | M 12 x 1.5 | M 22 x 1.5 | M 22 x 1.5 | 12 | 25 | 20 | 25 | 33 | 27 |
| K 440-47 | 6 | M 12 x 1.5 | M 22 x 1.5 | M 26 x 1.5 | 15 | 25 | 23 | 25 | 33 | 27 |

AF = Width across flats

Product versions

| | |
|------------------------------|--|
| K 44-35 - K 44-66 | Reducing connecting fitting, T shaped, with union nut, cutting ring, pressure ring, sealing ring and counter nut |
| K 44-38 / K 44-82 | Connecting fitting, T shaped, with union nut, cutting ring and counter nut |
| K 44-48 | Reducing connecting fitting, T shaped, with union nut, cutting ring, pressure ring and sealing ring. |
| K 46-12-5 / K 46-12-9 | Connecting fitting, T shaped with test connection, with union nut, cutting ring, pressure ring, sealing ring and test connection |
| K 47-20 | Connecting fitting, T shaped, Steel |