

Properties				
Connection 1	metric cylindrical outer thread			
Sealing form 1	24° inner cone			
Connection 2 + 3	metric cylindrical outer thread			
Sealing form 2 + 3	Butt construction			
Construction	T shaped			
Material	Steel			
Surface	electro galvanised			



Item										
Identification	Ø d2	G1	G2	G3	j1	i2	L1	L2	L3	AF
	(mm)				(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
K 440-28	10	M 16 x 1.5	M 22 x 1.5	M 22 x 1.5	12	25	20	25	33	27
K 440-35	6	M 12 x 1.5	M 22 x 1.5	M 22 x 1.5	12	25	20	25	33	27
K 440-47	6	M 12 x 1.5	M 22 x 1.5	M 26 x 1.5	15	25	23	25	33	27

AF = Width across flats

Product versions			
K 44-35 - K 44-66	Reducing connecting fitting, T shaped, with union nut, cutting ring, pressure ring, sealing ring and counter nut		
K 44-38 / K 44-82	Connecting fitting, T shaped, with union nut, cutting ring and counter nut		
K 44-48	Reducing connecting fitting, T shaped, with union nut, cutting ring, pressure ring and sealing ring.		
K 46-12-5 / K 46-12-9	Connecting fitting, T shaped with test connection, with union nut, cutting ring, pressure ring, sealing ring and test connection		
K 47-20	Connecting fitting, T shaped, Steel		