

K 440-52 / K 440-127

Screw-in socket, T shaped

HANSA FLEX

Properties

Connection 1	metric cylindrical outer thread
Sealing form 1	Butt construction
Connection 2 + 3	metric cylindrical outer thread
Sealing form 2 + 3	24° inner cone
Construction	T shaped
Material	Steel
Surface	electro galvanised



Item

Identification	Ø d2 (mm)	Ø d3 (mm)	G1	G2	G3	i (mm)	L1 (mm)	L2 (mm)	L3 (mm)	AF (mm)
K 440-103	12	6	M 16 x 1.5	M 18 x 1.5	M 12 x 1.5	20	24	37	17	17
K 440-52	12	-	M 16 x 1.5	M 18 x 1.5	M 18 x 1.5	20	24	37	17	17
K 440-87	12	-	M 22 x 1.5	M 18 x 1.5	M 18 x 1.5	24	26	42	19	17
K 440-92	8	-	M 22 x 1.5	M 14 x 1.5	M 14 x 1.5	24	26	42	19	17
K 440-109	10	-	M 22 x 1.5	M 16 x 1.5	M 16 x 1.5	24	26	42	19	17
K 440-127	10	-	M 16 x 1.5	M 16 x 1.5	M 16 x 1.5	20	24	37	17	14

Ø d2 / Ø d3 = External pipe diameter – AF = Width across flats

Product versions

K 44-75 - K 44-169 Screw in fitting, with union nut, cutting ring, counter nut, pressure ring and cord ring