

# K 440-52 / K 440-127

Screw-in socket, T shaped

## Properties

**Connection 1** metric cylindrical outer thread

**Sealing form 1** Butt construction

**Connection 2 + 3** metric cylindrical outer thread

**Sealing form 2 + 3** 24° inner cone

**Construction** T shaped

**Material** Steel

**Surface** electro galvanised



## Item

Identification	Ø d2 (mm)	Ø d3 (mm)	G1	G2	G3	i (mm)	L1 (mm)	L2 (mm)	L3 (mm)	AF (mm)
<b>K 440-103</b>	12	6	M 16 x 1.5	M 18 x 1.5	M 12 x 1.5	20	24	37	17	17
<b>K 440-52</b>	12	-	M 16 x 1.5	M 18 x 1.5	M 18 x 1.5	20	24	37	17	17
<b>K 440-87</b>	12	-	M 22 x 1.5	M 18 x 1.5	M 18 x 1.5	24	26	42	19	17
<b>K 440-92</b>	8	-	M 22 x 1.5	M 14 x 1.5	M 14 x 1.5	24	26	42	19	17
<b>K 440-109</b>	10	-	M 22 x 1.5	M 16 x 1.5	M 16 x 1.5	24	26	42	19	17
<b>K 440-127</b>	10	-	M 16 x 1.5	M 16 x 1.5	M 16 x 1.5	20	24	37	17	14

Ø d2 / Ø d3 = External pipe diameter – AF = Width across flats

## Product versions

**K 44-75 - K 44-169** Screw in fitting, with union nut, cutting ring, counter nut, pressure ring and cord ring