

# K 440-55 - K 440-122

Screw-in socket, L shaped

**HANSA FLEX**

## Properties

**Connection 1** metric cylindrical outer thread

**Sealing form 1** Butt construction

**Connection 2 + 3** metric cylindrical outer thread

**Sealing form 2 + 3** 24° inner cone

**Construction** L shaped

**Material** Steel

**Surface** electro galvanised



## Item

Identification	Ø d2 (mm)	Ø d3 (mm)	G1	G2	G3	i (mm)	L1 (mm)	L2 (mm)	L3 (mm)	AF (mm)
K 440-55	12	12	M 18 x 1.5	M 18 x 1.5	M 16 x 1.5	20	28	35	21	17
K 440-76	6	12	M 12 x 1.5	M 18 x 1.5	M 16 x 1.5	24	24	38	17	17
K 440-77	8	12	M 14 x 1.5	M 18 x 1.5	M 16 x 1.5	24	24	38	17	17
K 440-99	12	12	M 18 x 1.5	M 18 x 1.5	M 22 x 1.5	24	24	42	17	17
K 440-108	10	10	M 16 x 1.5	M 16 x 1.5	M 22 x 1.5	24	24	42	17	17
K 440-95	12	8	M 18 x 1.5	M 14 x 1.5	M 22 x 1.5	24	24	32	17	17
K 440-104	10	12	M 16 x 1.5	M 18 x 1.5	M 16 x 1.5	20	28	35	21	17
K 440-111	10	10	M 16 x 1.5	M 16 x 1.5	M 16 x 1.5	24	24	40	17	14
K 440-122	10	10	M 16 x 1.5	M 16 x 1.5	M 12 x 1.5	24	24	38	17	14

Ø d2 / Ø d3 = External pipe diameter – AF = Width across flats

## Product versions

**K 44-76 - K 44-160** Screw-in fitting, L shaped, with union nut, cutting ring, counter nut, pressure ring and cord ring