K 440-55 - K 440-122

Screw-in socket, L shaped

Properties

Connection 1	metric cylindrical outer thread
Sealing form 1	Butt construction
Connection 2 + 3	metric cylindrical outer thread
Sealing form 2 + 3	24° inner cone
Construction	L shaped
Material	Steel
Surface	electro galvanised



Item

Identification	Ø d2 (mm)	Ø d3 (mm)	G1	G2	G3	i (mm)	L1 (mm)	L2 (mm)	L3 (mm)	AF (mm)
K 440-55	12	12	M 18 x 1.5	M 18 x 1.5	M 16 x 1.5	20	28	35	21	17
K 440-76	6	12	M 12 x 1.5	M 18 x 1.5	M 16 x 1.5	24	24	38	17	17
K 440-77	8	12	M 14 x 1.5	M 18 x 1.5	M 16 x 1.5	24	24	38	17	17
K 440-99	12	12	M 18 x 1.5	M 18 x 1.5	M 22 x 1.5	24	24	42	17	17
K 440-108	10	10	M 16 x 1.5	M 16 x 1.5	M 22 x 1.5	24	24	42	17	17
K 440-95	12	8	M 18 x 1.5	M 14 x 1.5	M 22 x 1.5	24	24	32	17	17
K 440-104	10	12	M 16 x 1.5	M 18 x 1.5	M 16 x 1.5	20	28	35	21	17
K 440-111	10	10	M 16 x 1.5	M 16 x 1.5	M 16 x 1.5	24	24	40	17	14
K 440-122	10	10	M 16 x 1.5	M 16 x 1.5	M 12 x 1.5	24	24	38	17	14

Ø d2 / Ø d3 = External pipe diameter – AF = Width across flats

Product versions

K 44-76 - K 44-160	Screw-in fitting, L shaped, with union nut, cutting ring, counter nut, pressure ring and cord ring

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.