

# K 46-4-21 - K 46-4-37

## Screw-in bulkhead fitting

### Properties

<b>Connection 1</b>	metric cylindrical outer thread
<b>Connection 2</b>	metric cylindrical outer thread
<b>Sealing form 2</b>	24° inner cone
<b>Design</b>	for bulkhead mounting
<b>Construction</b>	straight
<b>Scope of supply</b>	with union nut, cutting ring and counter nut
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



### Item

Identification	Ø d2 (mm)	G1	G2	i (mm)	L1 (mm)	AF (mm)	S1	S2
<b>K 46-4-21</b>	12	M 16 x 1.5	M 18 x 1.5	12	62	22	24	22
<b>K 46-4-22</b>	12	M 22 x 1.5	M 18 x 1.5	12	62	27	24	22
<b>K 46-4-34</b>	10	M 22 x 1.5	M 16 x 1.5	12	60	27	22	19
<b>K 46-4-37</b>	10	M 16 x 1.5	M 16 x 1.5	12	62	22	22	19

AF = Width across flats

### Product versions

<b>K 460-4-19 - K 460-4-29</b>	Screw-in socket for bulkhead fitting, Steel
--------------------------------	---