

# K 46-4-23 - K 46-4-40

Screw-in bulkhead fitting

**HANSA FLEX**

## Properties

<b>Connection 1</b>	metric cylindrical outer thread
<b>Connection 2</b>	metric cylindrical outer thread
<b>Design</b>	for bulkhead mounting
<b>Construction</b>	straight
<b>Scope of supply</b>	with union nut, cutting ring, pressure ring, sealing ring and counter nut
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Item

Identification	Ø d2 (mm)	G1	G2	i (mm)	L1 (mm)	AF (mm)	S1	S2
<b>K 46-4-23</b>	16	M 22 x 1.5	M 22 x 1.5	12	76	27	27	27
<b>K 46-4-32</b>	15	M 22 x 1.5	M 18 x 1.5	12	76	27	24	22
<b>K 46-4-36</b>	15	M 22 x 1.5	M 22 x 1.5	12	76	27	27	27
<b>K 46-4-39</b>	15	M 16 x 1.5	M 22 x 1.5	12	76	27	27	27
<b>K 46-4-40</b>	18	M 22 x 1.5	M 26 x 1.5	12	76	32	32	32

AF = Width across flats

## Product versions

**K 460-4-6 - K 460-4-31** Screw-in sockets, Steel