

# K 46-1-35 / K 46-1-62

Screw-in bulkhead socket, test connection

**HANSA FLEX**

## Properties

|                          |  |
|--------------------------|--|
| <b>Connection 1</b>      | metric cylindrical outer thread  |
| <b>Sealing form 1</b>    | 24° inner cone   |
| <b>Connection 2</b>      | metric cylindrical outer thread  |
| <b>Sealing form 2</b>    | Butt construction  |
| <b>Connection 3</b>      | BSP cylindrical internal threads   |
| <b>Design</b>            | for bulkhead mounting  |
| <b>Construction type</b> | with test connection   |
| <b>Construction</b>      | straight   |
| <b>Scope of supply</b>   | with union nut, cutting ring, sealing ring, counter nut, and test connection |
| <b>Material</b>          | Steel  |
| <b>Surface</b>           | electro galvanised   |



## Item

| Identification   | Ø d2<br>(mm) | G1         | i<br>(mm) | L1<br>(mm) | L2<br>(mm) | L3<br>(mm) | AF<br>(mm) | S1 | S2 |
|------------------|--------------|------------|-----------|------------|------------|------------|------------|----|----|
| <b>K 46-1-62</b> | 12           | M 22 x 1.5 | 25        | 65         | 35         | 47         | 27         | 22 | 27 |

AF = Width across flats