K 460-4-6 - K 460-4-31

Screw-in sockets

Properties

Connection 1	metric cylindrical outer thread
Connection 2	metric cylindrical outer thread
Sealing form 2	Butt construction
Design	for bulkhead mounting
Construction	straight
Material	Steel
Surface	electro galvanised



Item

Identification	G1	G2	i1 (mm)	i2 (mm)	L1 (mm)	AF (mm)
K 460-4-6	M 22 x 1.5	M 22 x 1.5	12	34	54	27
K 460-4-7	M 22 x 1.5	M 12 x 1.5	12	20	40	27
K 460-4-8	M 22 x 1.5	M 14 x 1.5	12	23	43	27

AF = Width across flats

Product versions

K 46-4-23 - K 46-4-40	Screw-in bulkhead fitting, with union nut, cutting ring, pressure ring, sealing ring and counter nut
K 46-4-6 / K 46-4-24	Connecting bulkhead fitting, with union nut, cutting ring, pressure ring, sealing ring and counter nut
K 46-4-7 - K 46-4-42	Screw-in socket for bulkhead fitting, with counter nut
K 47-07 / K 47-41	Connecting fitting, with union nut, cutting ring, pressure ring, sealing ring, counter nut and hose fitting

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.