

K 42-02 - K 42-106

Screw in fitting

HANSA FLEX

Properties

Connection 1	metric cylindrical outer thread
Sealing form 1	Shape A
Connection 2	metric cylindrical outer thread
Sealing form 2	24° inner cone
Construction	straight
Scope of supply	with union nut and cutting ring
Material	Steel
Surface	electro galvanised



Item

Identification	Ø d2 (mm)	G1	D (mm)	i (mm)	L1 (mm)	L2 (mm)	AF (mm)	S1
K 42-02	6	M 12 x 1.5	17	12	36,5	22,0	17	14
K 42-09	8	M 12 x 1.5	17	12	37,0	22,0	17	17
K 42-10	8	M 14 x 1.5	19	12	37,0	22,0	19	19
K 42-15	10	M 14 x 1.5	19	12	38,0	23,0	19	19
K 42-17	10	M 16 x 1.5	21	12	39,5	24,5	22	19
K 42-31	15	M 18 x 1.5	23	12	40,5	25,5	24	27
K 42-40	18	M 22 x 1.5	27	14	45,0	28,5	27	32
K 42-106	12	M 16 x 1.5	21	12	39,5	24,5	22	22

Ø d2 = External pipe diameter – AF = Width across flats

Product versions

K 420-03 - K 420-84 Screw-in sockets, Steel