

# UEM FM
Union function nut

HANSA-FLEX

## Properties

| | |
|---|---|
| **Connection 1** | metric nut thread |
| **Design** | Union function nut |
| **Scope of supply** | Union nut, cutting ring, soft seal |
| **Material** | Steel |
| **Surface** | electro galvanised |






## Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

## Item

| Identification | Series | Operating pressure | Ø d2 (mm) | G1 | L1 (mm) | S1 |
|---|---|---|---|---|---|---|
| **UEM 04 FM LL** | LL | PN 100 | 4 | M 8 x 1 | 11,0 | 10 |
| **UEM 06 FM LL** | LL | PN 100 | 6 | M 10 x 1 | 11,5 | 12 |
| | | | | | | |
| **UEM NW 04 FM L** | L | PN 315 | 6 | M 12 x 1.5 | 14,5 | 14 |
| **UEM NW 06 FM L** | L | PN 315 | 8 | M 14 x 1.5 | 14,5 | 17 |
| **UEM NW 08 FM L** | L | PN 315 | 10 | M 16 x 1.5 | 15,5 | 19 |
| **UEM NW 10 FM L** | L | PN 315 | 12 | M 18 x 1.5 | 15,5 | 22 |
| **UEM NW 13 FM L** | L | PN 315 | 15 | M 22 x 1.5 | 17,0 | 27 |
| **UEM NW 16 FM L** | L | PN 315 | 18 | M 26 x 1.5 | 18,0 | 32 |
| **UEM NW 20 FM L** | L | PN 160 | 22 | M 30 x 2 | 20,0 | 36 |
| **UEM NW 25 FM L** | L | PN 160 | 28 | M 36 x 2 | 21,0 | 41 |
| **UEM NW 32 FM L** | L | PN 160 | 35 | M 45 x 2 | 24,0 | 50 |
| **UEM NW 40 FM L** | L | PN 160 | 42 | M 52 x 2 | 24,0 | 60 |
| | | | | | | |
| **UEM NW 03 FM S** | S | PN 630 | 6 | M 14 x 1.5 | 16,5 | 17 |
| **UEM NW 04 FM S** | S | PN 630 | 8 | M 16 x 1.5 | 16,5 | 19 |
| **UEM NW 06 FM S** | S | PN 630 | 10 | M 18 x 1.5 | 17,5 | 22 |
| **UEM NW 08 FM S** | S | PN 630 | 12 | M 20 x 1.5 | 17,5 | 24 |
| **UEM NW 10 FM S** | S | PN 630 | 14 | M 22 x 1.5 | 20,5 | 27 |
| **UEM NW 13 FM S** | S | PN 400 | 16 | M 24 x 1.5 | 20,5 | 30 |
| **UEM NW 16 FM S** | S | PN 400 | 20 | M 30 x 2 | 24,0 | 36 |
| **UEM NW 20 FM S** | S | PN 400 | 25 | M 36 x 2 | 27,0 | 46 |
| **UEM NW 25 FM S** | S | PN 400 | 30 | M 42 x 2 | 29,0 | 50 |
| **UEM NW 32 FM S** | S | PN 315 | 38 | M 52 x 2 | 32,5 | 60 |

Series: LL = Very light  L = Light  S = Heavy – Ø d2 = External pipe diameter

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*