

# SKM HL 3 UDK

Push-in coupling female

**HANSA FLEX**

## Properties

|                           |                                      |
|---------------------------|--------------------------------------|
| <b>Connection 1</b>       | metric cylindrical outer thread      |
| <b>Sealing form 1</b>     | 24° inner cone                       |
| <b>Additional feature</b> | for coupling under residual pressure |
| <b>Material</b>           | Steel                                |
| <b>Surface</b>            | electro galvanised                   |



## Item

| Identification         | DN* | Series | for external pipe Ø (mm) | Connecting thread | AF (mm) | Size | Operating pressure (bar) | D1 (mm) | D2 (mm) | L (mm) | SF coup.* | Mineral oil temp. min. (°C) | Mineral oil temp. max. (°C) |
|------------------------|-----|--------|--------------------------|-------------------|---------|------|--------------------------|---------|---------|--------|-----------|-----------------------------|-----------------------------|
| <b>SKM 10 HL 3 UDK</b> | 10  | L      | 12                       | M 18x1,5          | 30      | 3    | 225,0                    | 38      | 23,8    | 70     | 4         | 25                          | 125                         |
| <b>SKM 13 HL 3 UDK</b> | 12  | L      | 15                       | M 22x1,5          | 30      | 3    | 225,0                    | 38      | 23,8    | 71     | 4         | 25                          | 125                         |

BD = Working pressure – SF gek. = Safety factor coupled – AF = Width across flats