


# TW OW

## Tank truck hose without helix



### Properties

<b>Application</b>	Winding hose for tankers
<b>Special features</b>	oil and petrol resistant pressure hose electrical resistance R less than 10,000,000 Ohm
<b>Standard</b>	NW 25: EN 1360; NW 32-40: EN 12115, NW 32-40: TRbF 131 Part 2
<b>Inner layer</b>	NBR
<b>Insert</b>	one textile braided insert with copper braid
<b>Outer layer</b>	NBR / SBR (patterned material)
<b>Colour</b>	black
<b>Temp. min.</b>	-20 °C
<b>Temp. max.</b>	65 °C
<b>Media</b>	All types of mineral oil products with a max. aromatic content of 50%



### Item

Identification	Inches	Internal Ø (mm)	Wall thickness (mm)	Operating pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)	Roll length (m)
TW OW 25	1"	25	6,0	16,0	64	150	40
TW OW 32	1.1/4"	32	6,0	16,0	64	190	40
TW OW 38	1.1/2"	38	6,5	16,0	64	230	40

### Accessories

<b>KS AL</b>	Clamp ring fitting, aluminium
<b>KS FIX AL</b>	Clamping shell for pinning, aluminium
<b>TW-TUE MG</b>	Tank truck fitting, brass
<b>TW-TUEG MG</b>	Tanker fitting, brass
<b>TW-TUEG VA</b>	Tank truck fitting, stainless steel
<b>TW-TG VA</b>	Tank truck fitting, stainless steel
<b>TW-TG MG</b>	Tanker fitting, brass
<b>TW-T MG</b>	Tank truck fitting, brass