

# WA IR RG

Connector ... IR, red bronze

## Properties

|                     |                                                             |
|---------------------|-------------------------------------------------------------|
| <b>Application</b>  | Connection fitting for metal hoses                          |
| <b>Connection 1</b> | Threaded bushing with cylindrical, imperial internal thread |
| <b>Standard</b>     | DIN EN 10226 / ISO 7-1                                      |
| <b>Construction</b> | straight                                                    |
| <b>Material</b>     | Red bronze                                                  |
| <b>Application</b>  | soldered variant temperature resistant up to 200 °C         |



## Ordering information

Other designs available on request

## Item

| Identification | DN | G1        |
|----------------|----|-----------|
| WA 013 IR RG   | 13 | Rp 1/2"   |
| WA 020 IR RG   | 20 | Rp 3/4"   |
| WA 025 IR RG   | 25 | Rp 1"     |
| WA 032 IR RG   | 32 | Rp 1.1/4" |
| WA 040 IR RG   | 40 | Rp 1.1/2" |
| WA 050 IR RG   | 50 | Rp 2"     |

## Product versions

|                 |                                                            |
|-----------------|------------------------------------------------------------|
| <b>WA IR</b>    | Connector ... IR, malleable cast iron, Malleable cast iron |
| <b>WA IR ST</b> | Connector ... IR, steel, Steel (weldable)                  |
| <b>WA IR VA</b> | Connector ... IR, VA, Stainless steel                      |