



HK BHQ

Connection plate for flow control valve QV

HANSA FLEX

Properties

Scope of supply	incl. set of screws
Operating pressure	max. 250 bar
Connection	ISO/Cetop 03 size 6



Description

The HK BHQ version permits the modular installation of HK QV 06 valves as sandwich plate with ISO/Cetop 03 hole pattern.

Item				
Identification	acts in channel	Design	Scope of supply	Weight (kg)
HK BHQ 011	P	without cover plate, drilled on one side	incl. screw set (4x M5 x 70)	0,7
HK BHQ 012	A + B	without cover plate	incl. screw set (8x M5 x 70)	0,7
HK BHQ 013	A	incl. cover plate	incl. screw set (4x M5 x 70)	0,7
HK BHQ 014	B	incl. cover plate	incl. screw set (4x M5 x 70)	0,7
HK BHQ 016	T	without cover plate, drilled on one side	incl. screw set (4x M5 x 70)	0,7
HK BHQ 022	A + B	without cover plate	incl. screw set (8x M5 x 70)	0,7
HK BHQ 023	A	incl. cover plate	incl. screw set (4x M5 x 70)	0,7
HK BHQ 024	B	incl. cover plate	incl. screw set (4x M5 x 70)	0,7

Accessory for following products

HK QV	Flow control valve for plate mounting Cetop
-------	---