

# HK BM150

Hand-operated directional control valve BM 150

**HANSA FLEX**

## Properties

<b>Design</b>	Monobloc valve for pipeline installation
<b>Scope of supply</b>	without hand lever (please order separately)
<b>Operating pressure</b>	P, A, B: max. 220bar / T: max. 80bar
<b>Volumetric flow</b>	max. 150 l/min (note characteristic curves)
<b>Connection</b>	P + T = G 3/4"; P2 + T2 = G 1"; A + B = G 3/4"



## Description

compact design

Integrated non-return valve and pressure relief valve 90-220bar (valve must be set)

spool with control notches for sensitive operation

only possible with 1 section

## Ordering information

Please order hand lever separately - 1 lever per section!

The valves are available in the stated basic version. For other possible configurations for actuators and piston types see graphic.

Example configuration HKBM150A1:

- Valve type HKBM150

- Section 1 with piston type A and actuator 1

## Item

Identification	Design	Weight (kg)
HK BM150 A1	1 Section (A1)	8,2

## Accessories

**HK BM HEB** Hand lever & accessories for hand-operated directl. control valve BM

**HK BM C0** Pressure transmission for hand-operated directional control valve BM

## Spare parts

**HK BM KOL** Piston for hand-operated directional control valve BM

**HK BM BET** Actuation for hand-operated directional control valve BM