

HK BSK

BSK hydraulic tank (with cleaning hatch)



Properties

Design	with cleaning hatch and gasket
Material	Steel Gasket: NBR



Note

Up to BG 200 with 1 cleaning hatch
Above BG 250 with 2 cleaning hatches
Drain bolt G1"

Description

Tanks of quality steel, sandblasted, primer coating inside and outside with high-quality zinc dust paint that is resistant to mineral-oil based hydraulic oils. All tanks are subjected to 100% leak test.

Ordering information

Viton gasket for cleaning hatch available on request.

Item

Identification	Useful volume V [l] (L)	B1 (mm)	H1 (mm)	L1 (mm)	B2 (mm)	L2 (mm)	H2 (mm)	B3 (mm)	L3 (mm)	Ø D1 (mm)	Ø D2 (mm)	S1 (mm)	S2 (mm)	S3 (mm)	Weight (kg)
HK BSK 40	38	375	430	508	315	428	280	30	-	200	250,0	3	3	6	33
HK BSK 63	59	375	560	508	315	428	410	30	-	248	324,0	3	3	6	42
HK BSK 100	92	474	560	633	414	553	407	30	-	248	324,0	4	4	6	63
HK BSK 160	152	604	560	810	544	730	410	30	-	248	324,0	4	4	6	88
HK BSK 200	184	654	560	900	594	820	410	30	-	248	324,0	4	4	6	101
HK BSK 250	235	704	580	1010	644	930	430	30	410	248	324,0	4	4	7	123
HK BSK 300	272	714	580	1208	654	1128	412	30	410	248	324,0	4	4	7	141
HK BSK 400	375	749	580	1514	689	1434	430	30	750	248	324,0	4	7	7	201

Accessories

HK OEWSK Oil tray for steel tank, Type BSK

Spare parts

HK BSK RD Cleaning hatch cover for steel tank, Type BSK