


HK DH01

Hand-operated directional control valve NG6

HANSA FLEX

Properties

Design	4/2-way valve or 4/3-way valve
Operating pressure	P, A, B: max. 350bar / T: max. 160bar
Volumetric flow	max. 50 l/min (note characteristic curves)
Connection	ISO/Cetop 03 size 6
Mounting	4 pcs. socket head screw M5x50 12.9



Description

Mechanical operation with hand lever
Hand lever mounted on side "A"

Ordering information

Further circuits and versions available on request

Item

Identification	Type	Overlap	Piston type	Design	Weight (kg)
HK DH01 20	4/2	negative (open)	0 [PB/AT]-[PA/BT]	Spring return	1,6
HK DH01 21	4/2	positive (closed)	1 [PB/AT]-[PA/BT]	Spring return	1,6
HK DH01 50	4/2	negative (open)	0 [PB/AT]-[PA/BT]	2 latching positions	1,6
HK DH01 51	4/2	positive (closed)	1 [PB/AT]-[PA/BT]	2 latching positions	1,6
HK DH01 10	4/3	negative (open)	0 [PB/AT]-[ABPT]-[PA/BT]	spring return to 0	1,6
HK DH01 11	4/3	positive (closed)	1 [PB/AT]-[A/B/P/T]-[PA/BT]	spring return to 0	1,6
HK DH01 13	4/3	positive (closed)	3 [PB/AT]-[ABT/P]-[PA/BT]	spring return to 0	1,6
HK DH01 14	4/3	negative (open)	4 [PA/BT]-[A/B/PT]-[PB/AT]	spring return to 0	1,6
HK DH01 40	4/3	negative (open)	0 [PB/AT]-[ABPT]-[PA/BT]	3 latching positions	1,6
HK DH01 41	4/3	positive (closed)	1 [PB/AT]-[A/B/P/T]-[PA/BT]	3 latching positions	1,6
HK DH01 43	4/3	positive (closed)	3 [PB/AT]-[ABT/P]-[PA/BT]	3 latching positions	1,6
HK DH01 44	4/3	negative (open)	4 [PA/BT]-[A/B/PT]-[PB/AT]	3 latching positions	1,6

Piston type example: [A/B/PT] = [A blocked / B blocked / P+T connected]

Accessories

HK M HK DH Screw set for NG 6 valves type HK DH / DG4V3