HK DH08/09

Directional control valve NG6, pneumatically controlled

Properties

Design	4/2-way valve or 4/3-way valve
Operating pressure	P, A, B: max. 350bar / T: max. 100bar
Volumetric flow	max. 50 l/min (note characteristic curves)
Connection	ISO/Cetop 03 size 6
Mounting	4 pcs. socket head screw M5x50 12.9





Description

Pneumatic actuation with emergency hand operation
Min. pneumatic control pressure 2 bar / recommended pneumatic control pressure 12 bar
Thread on control pressure port 1/8" female thread

Ordering information

Further circuits and versions available on request

Item

Identification	Type	Overlap	Piston type		Design	Weight (kg)
HK DH08 10	4/2	negative (open)	0	[PB/AT]-[ABPT]	Spring return	1,2
HK DH08 31 2	4/2	positive (closed)	1	[PB/AT]-[PA/BT]	Spring return	1,2
HK DH09 10	4/3	negative (open)	0	[PB/AT]-[ABPT]-[PA/BT]	spring return to 0	1,2
HK DH09 11	4/3	positive (closed)	1	[PB/AT]-[A/B/P/T]-[PA/BT]	spring return to 0	1,2
HK DH09 13	4/3	positive (closed)	3	[PB/AT]-[ABT/P]-[PA/BT]	spring return to 0	1,2
HK DH09 14	4/3	negative (open)	4	[PA/BT]-[A/B/PT]-[PB/AT]	spring return to 0	1,2

Piston type example: [A/B/PT] = [A blocked / B blocked / P+T connected]

Accessories

HK M HK DH	Screw set for NG 6 valves type HK DH / DG4V3

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.