


Properties				
Design	4/2-way valve or 4/3-way valve			
Operating pressure	P, A, B: max. 315bar / T: max. 160bar			
Volumetric flow	max. 100 l/min (note characteristic curves)			
Connection	ISO/Cetop 05 size 10			
Mounting	4 pcs. socket head screw M6x40 12.9			





Description

Mechanical operation with hand lever Hand lever mounted on side "A"

Ordering information

Further circuits and versions available on request

ltem .								
Identification	Туре	Overlap	Piston type		Design	Weight (kg)		
HK DK11 20	4/2	negative (open)	0	[PB/AT]-[PA/BT]	Spring return	2,5		
HK DK11 21	4/2	positive (closed)	1	[PB/AT]-[PA/BT]	Spring return	2,5		
HK DK11 50	4/2	negative (open)	0	[PB/AT]-[PA/BT]	2 latching positions	2,5		
HK DK11 51	4/2	positive (closed)	1	[PB/AT]-[PA/BT]	2 latching positions	2,5		
HK DK11 10	4/3	negative (open)	0	[PB/AT]-[ABPT]-[PA/BT]	spring return to 0	2,8		
HK DK11 11	4/3	positive (closed)	1	[PB/AT]-[A/B/P/T]-[PA/BT]	spring return to 0	2,8		
HK DK11 13	4/3	positive (closed)	3	[PB/AT]-[ABT/P]-[PA/BT]	spring return to 0	2,8		
HK DK11 14	4/3	negative (open)	4	[PA/BT]-[A/B/PT]-[PB/AT]	spring return to 0	2,8		
HK DK11 40	4/3	negative (open)	0	[PB/AT]-[ABPT]-[PA/BT]	3 latching positions	2,8		
HK DK11 41	4/3	positive (closed)	1	[PB/AT]-[A/B/P/T]-[PA/BT]	3 latching positions	2,8		
HK DK11 43	4/3	positive (closed)	3	[PB/AT]-[ABT/P]-[PA/BT]	3 latching positions	2,8		
HK DK11 44	4/3	negative (open)	4	[PA/BT]-[A/B/PT]-[PB/AT]	3 latching positions	2,8		

Piston type example: [A/B/PT] = [A blocked / B blocked / P+T connected]

Accessories	3
HK M HK DK	Set of bolts for NG 10 valves types HK DK11/DKE/DG4V5