HK K C E-Motor 24V


DC 24V electric motor

HANSA-FLEX

Properties

Design	Direct current motor for industrial applications
Voltage	24 V





Item

Identificatic	A (mm)	Ø B (mm)	Design	Po-wer (kW)	Direction of rotation	Speed max. (rpm)	Cyclic duration factor S2 operation (min)	Cyclic duration factor S3 operation (%)	Protec-tion class	Shaft	Weig-ht (kg)
HK KC 41	158,5	80,0	-	0,5	reversible	2800	5,0	17,0	IP 54	type Y Ø15.6 x 6.5 x 10.5	2,60
HK KC 79	215,5	112,5	with fan	2,0	clockwise rotating	2200	4,5	10,0	IP 23	type X Ø17.9 x 8.3 x 9.0	7,75
HK KC 92	173,5	114,0	-	2,2	clockwise rotating	2600	1,2	4,5	IP 54	type X Ø17.9 x 8.3 x 9.0	6,90
HK KC 94	158,5	80,0	-	0,8	reversible	4000	2,5	8,0	IP 54	type Y Ø15.6 x 6.5 x 10.5	2,60
HK KC 95	237,0	131,0	-	3,0	clockwise rotating	2600	4,0	15,0	IP 54	type X Ø16.8 x 8.0 x 7.0	12,60
HK KC 97	183,0	114,0	-	2,0	clockwise rotating	2200	2,0	5,0	IP 54	type X Ø17.9 x 8.3 x 9.0	7,16
HK KC 103	173,5	114,0	with thermal contact	2,2	clockwise rotating	2600	1,2	4,5	IP 54	type X Ø17.9 x 8.3 x 9.0	6,70
HK KC 104	209,0	131,0	with thermal contact	3,0	clockwise rotating	2600	4,0	15,0	IP 54	type X Ø16.8 x 8.0 x 7.0	12,50
HK KC 111	237,0	131,0	with fan	3,0	clockwise rotating	3300	6,0	20,0	IP 12	type X Ø16.8 x 8.0 x 7.0	12,50

Accessories

HK K REL	Start relay for DC electric motor
HK K CAP	Cap for DC electric motors

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.