

# HK ML32

## PTO shaft gearboxes

### Properties

<b>Material</b>	Aluminium housing
<b>Use</b>	For European standard gear pumps BG2



### Note

Direction of rotation:

Pump anti-clockwise rotating - PTO shaft of the gearbox clockwise rotating

Pump clockwise rotating - PTO shaft of the gearbox anti-clockwise rotating

### Ordering information

A coupling hub BF2T is required for the connection between pump and gearbox.

Gear unit is supplied without oil (SAE 85W-90 is recommended)

### Item

Identification	n1 max. (rpm)	M1 max. (N-m)	n2 max. (rpm)	M2 max. (N-m)	n2/n1	Connection, drive side	Weight (kg)
HK ML32 11 3.8	540	159	2052	42	3,8	Profile shaft - 1.3/8" - DIN 9611	4,3
HK ML32 21 3.8	540	159	2052	42	3,8	Hollow shaft - 1.3/8" - DIN 9611	4,3
HK ML32 31 3.8	540	159	2052	42	3,8	Hollow shaft with locking - 1.3/8" - DIN 9611	4,3

M1 = max. input torque – M2 = max. output torque – n1 = max. input speed – n2 = max. output speed

### Accessories

HK BF	Coupling hub
-------	--------------