

## Properties

<b>Material</b>	Aluminium housing
<b>Use</b>	For European standard gear pumps BG3



## Note

Direction of rotation:

Pump anti-clockwise rotating - PTO shaft of the gearbox clockwise rotating

Pump clockwise rotating - PTO shaft of the gearbox anti-clockwise rotating

## Ordering information

A coupling hub BF3 is required for the connection between pump and gearbox.

Gear unit is supplied without oil (SAE 85W-90 is recommended)

## Item

Identification	n1 max. (rpm)	M1 max. (N-m)	n2 max. (rpm)	M2 max. (N-m)	n2/n1	Connection, drive side	Weight (kg)
<b>HK ML52 11 3.8</b>	540	437	2057	115	3,8	Profile shaft - 1.3/8" - DIN 9611	7,8
<b>HK ML52 21 3.8</b>	540	437	2057	115	3,8	Hollow shaft - 1.3/8" - DIN 9611	7,8
<b>HK ML52 31 3.8</b>	540	437	2057	115	3,8	Hollow shaft with locking - 1.3/8" - DIN 9611	7,8

M1 = max. input torque – M2 = max. output torque – n1 = max. input speed – n2 = max. output speed

## Accessories

<b>HK BF</b>	Coupling hub
--------------	--------------