


# HK MPS R/S

Filter head for spin-on filter MPS

## Properties

Material Aluminium



## Description

With these filter heads, spin-on filters can be used as return flow filters (R) or suction filters (S)

Opening pressure of bypass valve for return filter (R): 1.75 bar

Opening pressure of bypass valve for suction filter (S): 0.3 bar

## Item

Identification	Line connection	Design	suitable for filter type MPS	Weight (kg)
HK MPS 050 070 RG1	G 3/4"	as return filter	050-070	0,36
HK MPS 100 150 RG1	G 1.1/4"	as return filter	100-150	1,00
HK MPS 200 250 RG1	G 1.1/2"	as return filter	200-250	1,22
HK MPS 300 350 RG1	G 1.1/2"	as return filter	300-350	2,86
HK MPS 050 070 SG1	G 3/4"	as suction filter	050-070	0,36
HK MPS 100 150 SG1	G 1.1/4"	as suction filter	100-150	1,00
HK MPS 200 250 SG1	G 1.1/2"	as suction filter	200-250	1,22
HK MPS 300 350 SF1	1.1/2" SAE 3000 PSI/M	as suction filter	300-350	2,86

## Spare part for following products

HK MPS 1	Spin-on filter type 1
HK MPS 2	Spin-on filter type 2
HK MPS 3	Spin-on filter type 3