
HK PFR
Radial piston pump





Description
Constant displacement pump with positive locking piston control
Low noise level
600 - 1800 rpm speed range
Incl. connection flange and screws

Ordering information
No stock goods, pumps are ordered on request.
Please note the special requirements on the couplings to be used (special ATOS couplings with balance weight) and the venting requirements when commissioning!

Item

Identification	VFU (cc)	Pressure max. (bar)	SAE pressure connection	SAE suction connection	Weight (kg)
HK PFR 202	1,7	500	SAE 3000	SAE 3000	12,0
HK PFR 203	3,7	500	SAE 3000	SAE 3000	12,0
HK PFR 206	5,8	350	SAE 3000	SAE 3000	12,0
HK PFR 308	8,2	350	SAE 3000	SAE 3000	31,0
HK PFR 311	11,4	350	SAE 3000	SAE 3000	31,0
HK PFR 315	14,7	350	SAE 3000	SAE 3000	31,0
HK PFR 518	18,1	350	SAE 3000	SAE 3000	38,0
HK PFR 522	21,8	350	SAE 3000	SAE 3000	38,0
HK PFR 525	25,4	350	SAE 3000	SAE 3000	38,0
HK PFR 530	29,6	250	SAE 3000	SAE 3000	39,0

VFU = conveying volume per revolution

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.