


Properties		
Connections	1/4" - male thread	
Material	Stainless steel	
Use	For gauge HK PTQCheck	





Description

Resistant to pressure peaks, extremely shock and vibration-resistant Output signal 4 to 20 mA Various measuring ranges up to 600 bar Measuring accuracy $\pm 0.5\%$ of range limit value Outer thread 1/4" fitting

Ordering information

Further accessories and gauges with additional options available on request.

Order adapter HFM MMD 1/4 (when connecting pressure transmitter and measuring turbine) separately

Item						
Identification	Measuring range	Pressure max.	Overload pressure max.	Connection	Weight (kg)	
HK PTA 101	-1 to 10 bar	10	20	G 1/4" - male thread	0,1	
HK PTA 060	0 to 60 bar	60	120	G 1/4" - male thread	0,1	
HK PTA 200	0 to 200 bar	200	400	G 1/4" - male thread	0,1	
HK PTA 400	0 to 400 bar	400	600	G 1/4" - male thread	0,1	
HK PTA 600	0 to 600 bar	600	800	G 1/4" - male thread	0,1	

Accessory for fo	ollowing products	
HK PTQ CHECK	Digital hand-held gauge, 5-channels	

Additional elements				
HK PML	PML Single instrumentation cable			
HK PQT	Combination instrumentation cable			
HFM MMD HKO	Measuring connection, M16 x 2 series			