

Properties

Connections	1/4" - male thread
Material	Stainless steel
Use	For gauge HK PTQCheck



Description

Resistant to pressure peaks, extremely shock and vibration-resistant
 Output signal 4 to 20 mA
 Various measuring ranges up to 600 bar
 Measuring accuracy $\pm 0.5\%$ of range limit value
 Outer thread 1/4" fitting

Ordering information

Further accessories and gauges with additional options available on request.
 Order adapter HFM MMD 1/4 (when connecting pressure transmitter and measuring turbine) separately

Item					
Identification	Measuring range	Pressure max. (bar)	Overload pressure max. (bar)	Connection	Weight (kg)
HK PTA 101	-1 to 10 bar	10	20	G 1/4" - male thread	0,1
HK PTA 060	0 to 60 bar	60	120	G 1/4" - male thread	0,1
HK PTA 200	0 to 200 bar	200	400	G 1/4" - male thread	0,1
HK PTA 400	0 to 400 bar	400	600	G 1/4" - male thread	0,1
HK PTA 600	0 to 600 bar	600	800	G 1/4" - male thread	0,1

Accessory for following products

HK PTQ CHECK	Digital hand-held gauge, 5-channels
--------------	-------------------------------------

Additional elements

HK PML	Single instrumentation cable
HK PQT	Combination instrumentation cable
HFM MMD HKO	Measuring connection, M16 x 2 series