

## Properties

<b>Connections</b>	1/4" - male thread
<b>Material</b>	Stainless steel
<b>Use</b>	For gauge HK PTQCheck



## Description

Resistant to pressure peaks, extremely shock and vibration-resistant  
 Output signal 4 to 20 mA  
 Various measuring ranges up to 600 bar  
 Measuring accuracy  $\pm 0.5\%$  of range limit value  
 Outer thread 1/4" fitting

## Ordering information

Further accessories and gauges with additional options available on request.  
 Order adapter HFM MMD 1/4 (when connecting pressure transmitter and measuring turbine) separately

## Item

Identification	Measuring range	Pressure max. (bar)	Overload pressure max. (bar)	Connection	Weight (kg)
HK PTA 101	-1 to 10 bar	10	20	G 1/4" - male thread	0,1
HK PTA 060	0 to 60 bar	60	120	G 1/4" - male thread	0,1
HK PTA 200	0 to 200 bar	200	400	G 1/4" - male thread	0,1
HK PTA 400	0 to 400 bar	400	600	G 1/4" - male thread	0,1
HK PTA 600	0 to 600 bar	600	800	G 1/4" - male thread	0,1

## Accessory for following products

HK PTQ CHECK	Digital hand-held gauge, 5-channels
--------------	-------------------------------------

## Additional elements

HK PML	Single instrumentation cable
HK PQT	Combination instrumentation cable
HFM MMD HKO	Measuring connection, M16 x 2 series