

HK SP DIN 43650

Electrical plug for solenoid coil DIN 43650 / ISO 4400

HANSA FLEX

Properties

Design	Plug with central screw, type A
Standard	EN 175301-803 (DIN 43650) / ISO 4400
Operating temperature	-40 °C to +125 °C
Scope of supply	incl. seal and M3 screw
Material	Housing: Polyamide Contacts: CuZn
protection class	IP 65



Item

Identification	Colour	Design	Weight (kg)
HK SP 664	black	standard 4-pin	0,07
HK SP 664 A	grey	standard 4-pin	0,07
HK SP 666	black	standard 3-pin	0,07
HK SP 666 A	grey	standard 3-pin	0,07
HK SP 667 24	transparent	with LED for 12/24 V DC	0,07
HK SP 667 110	transparent	with LED for 110 V AC	0,07
HK SP 667 220	transparent	with LED for 230 V AC	0,07
HK SP 668 24	transparent / black	with LED 12/24 V and protective circuit	0,07
HK SP 668 24 A	transparent / grey	with LED 12/24 V and protective circuit	0,07
HK SP 669	black	with rectifier	0,07
HK SP 669 A	grey	with rectifier	0,07

Accessory for following products

HK SP EMDV	Coil for cartridge valve EMDV
HK SP 770	Coil for cartridge valve SUN
HK SP DFE	Coil for solenoid-operated directional control valve HK DFE
HK SP 41C	Coil for HK41C solenoid-operated valve
HK SP 42C	Coil for solenoid-operated directional control valve HK42C
HK SP CAE	Coil for solenoid-operated directional control valve HK DKE
HK SP CAER	Coil for solenoid-operated directional control valve HK DKER
HK SP CO	Coil for HKDH solenoid-operated valve