

HK SP DIN 43650

Electrical plug for solenoid coil DIN 43650 / ISO 4400

HANSA**FLEX**

Properties

| | |
|-----------------------|--------------------------------------|
| Design | Plug with central screw, type A |
| Standard | EN 175301-803 (DIN 43650) / ISO 4400 |
| Operating temperature | -40 °C to +125 °C |
| Scope of supply | incl. seal and M3 screw |
| Material | Housing: Polyamide Contacts: CuZn |
| protection class | IP 65 |



Item

| Identification | Colour | Design | Weight (kg) |
|----------------|---------------------|---|-------------|
| HK SP 664 | black | standard 4-pin | 0,07 |
| HK SP 664 A | grey | standard 4-pin | 0,07 |
| HK SP 666 | black | standard 3-pin | 0,07 |
| HK SP 666 A | grey | standard 3-pin | 0,07 |
| HK SP 667 24 | transparent | with LED for 12/24 V DC | 0,07 |
| HK SP 667 110 | transparent | with LED for 110 V AC | 0,07 |
| HK SP 667 220 | transparent | with LED for 230 V AC | 0,07 |
| HK SP 668 24 | transparent / black | with LED 12/24 V and protective circuit | 0,07 |
| HK SP 668 24 A | transparent / grey | with LED 12/24 V and protective circuit | 0,07 |
| HK SP 669 | black | with rectifier | 0,07 |
| HK SP 669 A | grey | with rectifier | 0,07 |

Accessory for following products

| | |
|------------|---|
| HK SP EMDV | Coil for cartridge valve EMDV |
| HK SP 770 | Coil for cartridge valve SUN |
| HK SP DFE | Coil for solenoid-operated directional control valve HK DFE |
| HK SP 41C | Coil for HK41C solenoid-operated valve |
| HK SP 42C | Coil for solenoid-operated directional control valve HK42C |
| HK SP CAE | Coil for solenoid-operated directional control valve HK DKE |
| HK SP CAER | Coil for solenoid-operated directional control valve HK DKER |
| HK SP CO | Coil for HKDH solenoid-operated valve |