
## Pressure relief valve



| Properties         |                                      |
|--------------------|--------------------------------------|
| Design             | Sandwich body valve pilot-controlled |
| Operating pressure | max. 350 bar                         |
| Volumetric flow    | max. 230 l/min                       |
| Connection         | ISO/Cetop 07 NG16                    |





## Note

These valves must be set according to the application.

## Description

Sandwich body valve for constructing sandwich arrangements with ISO/Cetop 07 size 16 valves

## Ordering information

Further sandwich body valves available on request

| itom                |                 |                             |                             |                   |                |  |  |
|---------------------|-----------------|-----------------------------|-----------------------------|-------------------|----------------|--|--|
| Identification      | acts in channel | Pressure setting range min. | Pressure setting range max. | Plate height (mm) | Weight<br>(kg) |  |  |
| HK ZP 16 DB 12 P 15 | Р               | 7                           | 105                         | 40                | 3,4            |  |  |
| HK ZP 16 DB 12 P 50 | Р               | 35                          | 350                         | 40                | 3,4            |  |  |
| HK ZP 16 DB 12 A 15 | A               | 7                           | 105                         | 40                | 3,4            |  |  |
| HK ZP 16 DB 12 A 50 | A               | 35                          | 350                         | 40                | 3,4            |  |  |
|                     |                 |                             |                             |                   |                |  |  |