HK S
Analogue Q gauge

HANSA-FLEX

Properties

Application	Volumetric flow measurement
Operating temperature max.	120 °C
Material	Stainless steel housing





Description

Independent of position, direct reading, one flow direction.
Linear gauge scale in l/min.
Sturdy and resistant to shock and vibration.
Accuracy ±2 % of range limit value.

Item

Identification	Thread	Measuring range	Pressure max. (bar)	L (mm)	Weight (kg)
HK 602 S 005	G 1/2”	2 to 20 l/min	420	168	0,90
HK 602 S 010	G 1/2”	4 to 37 l/min	420	168	0,90
HK 602 S 015	G 1/2”	5 to 55 l/min	420	168	0,90
HK 702 S 020	G 3/4”	10 to 75 l/min	350	183	1,75
HK 702 S 030	G 3/4”	10 to 115 l/min	350	183	1,75
HK 762 S 040	G 1"	10 to 150 l/min	350	183	1,75
HK 762 S 050	G 1"	20 to 190 l/min	350	183	1,75
HK 802 S 075	G 1.1/4”	40 to 280 l/min	350	310	8,00
HK 802 S 100	G 1.1/4”	50 to 370 l/min	350	310	8,00
HK 802 S 150	G 1.1/4”	50 to 560 l/min	350	310	8,00

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.