


## Properties

<b>Application</b>	Construction industry Agricultural technology
<b>Special features</b>	extremely durable, flexible, resistant to pressure and abrasion, UV and weatherproof slightly ribbed outer cover
<b>Inner layer</b>	stable, high flexibility, smooth plasticised PVC
<b>Insert</b>	impact and pressure resistant PVC reinforcing spiral
<b>Outer layer</b>	stable, high flexibility, smooth plasticised PVC
<b>Temp. min.</b>	-5 °C
<b>Temp. max.</b>	60 °C
<b>Media</b>	Water



## Note

All "-6" designations for example do not refer to the wall thickness

## Item

Identification	Inches	Internal Ø (mm)	Wall thickness (mm)	BD* at 20°C (bar)	Burst pressure (bar)	Vacuum (bar)	Min. bending radius (mm)	Roll length (m)
PVC WAS 19-6	3/4"	19	3,0	8,0	25	0,7	85	50
PVC WAS 25-7	1"	25	3,0	7,0	21	0,6	105	50
PVC WAS 32-6	1.1/4"	32	3,0	6,0	21	0,6	125	50
PVC WAS 38-6	1.1/2"	38	3,5	6,0	18	0,6	150	50
PVC WAS 50-5	2"	51	4,5	5,0	15	0,6	205	50
PVC WAS 60-4.5	2.1/2"	60	4,5	4,5	13	0,6	248	50
PVC WAS 76-3.5	3"	76	4,5	3,5	12	0,6	320	50
PVC WAS 90-3.5	3.1/2"	90	5,0	3,0	11	0,6	395	50

BD = Working pressure