


# MILK SD

## Food hose

### Properties

<b>Application</b>	Food industry
<b>Special features</b>	Phthalate-free tested in accordance with 1907/2006 / EC (REACH)
<b>Approval</b>	Fulfils FDA 21 CFR 177.2600 BFR RECOMMENDATION XXI CAT 2 DM 21.03.73 E SEGUENTI EUROPEAN REGULATION 1935/2004/EC JAPAN-MINISTRY OF HEALTH AND WELFARE NOTICE NO.370,1959 AND NO.201,2006
<b>Inner layer</b>	odourless, toxin-free special NBR rubber, generally suitable for use with foodstuffs, white
<b>Insert</b>	highly tear-resistant synthetic textile insert and steel wire spiral
<b>Outer layer</b>	synthetic rubber with high ozone, abrasion, and weather resistance
<b>Standard</b>	In keeping with European standards and FDA guideline
<b>Colour</b>	blue
<b>Temp. min.</b>	-40 °C
<b>Temp. max.</b>	80 °C
<b>Media</b>	Milk Cooking oil etc.



### Note

For cleaning with detergents, the hose is capable of withstanding temperatures up to 110°C for short periods.

### Item

Identification	Inches	Internal Ø (mm)	External Ø (mm)	Wall thickness (mm)	Operating pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)	Roll length (m)
<b>MILK SD 38-7</b>	1.1/2"	38,0	52,0	7,0	10,0	30	120	40
<b>MILK SD 40-7</b>	1.1/2"	38,0	50,0	6,0	10,0	30	115	40
<b>MILK SD 45-7</b>	1.3/4"	44,5	59,0	7,0	10,0	30	140	40
<b>MILK SD 63-7.5</b>	2.1/2"	63,5	75,5	6,0	10,0	30	190	40
<b>MILK SD 51-7.5</b>	2"	50,8	66,0	7,5	10,0	30	160	40
<b>MILK SD 75-8</b>	3"	76,0	90,0	7,0	10,0	30	230	40