


WA FL

Connector ... FL, steel

HANSA FLEX

Properties

Application	Connection fitting for metal hoses
Connection 1	Pipe sockets
Sealing form 1	Cutting ring connection
Standard	ISO 8434-1 DIN 3861
Short code	BEL
Construction	straight
Series	light
Material	Steel (weldable)



Note

Final cutting ring assembly must be carried out in the hardened pre-assembly socket (VOM...).
As an alternative we recommend connector shape AFL or AOL.

Ordering information

Other designs available on request

Item	Identification	DN	PN (bar)	Series	D1 (mm)	s (mm)	L1 (mm)
	WA 004 FL	4	250	6 L	6	1,0	25
	WA 006 FL	6	250	8 L	8	1,0	30
	WA 008 FL	8	250	10 L	10	1,0	30
	WA 010 FL	10	219	12 L	12	1,0	30
	WA 013 FL	13	250	15 L	15	1,5	32
	WA 016 FL	16	160	18 L	18	1,5	32
	WA 020 FL	20	160	22 L	22	1,5	36
	WA 025 FL	25	100	28 L	28	2,0	40
	WA 032 FL	32	100	35 L	35	2,0	45
	WA 040 FL	40	100	42 L	42	2,0	45

Product versions

WA FL CU	Connector ... FL, copper, Copper
WA FL VA	Connector ... FL, VA, Stainless steel 1.4571