


Properties			
Application	Connection fitting for metal hoses		
Connection 1	imperial outer thread, conical		
Sealing form 1	conical seat		
Standard	DIN EN 10226 / ISO 7-1		
Application	soldered variant temperature resistant up to 200 °C		
Construction	straight		
Design	3-part threaded connection		
Material	Malleable cast iron		





Note

Width across flats values are listed for reference purposes!

The specified working pressure PN(bar) relates to the working temperature of -20 °C to 120 °C. At working temperature of 120 °C to 200 °C the working pressure PN (bar) reduces to 22,7 bar.

Ordering information

Other designs available on request

Item				
Identification	DN	PN (bar)	G1	S1 (mm)
WA 006 VC	6	25	R 1/4"	28,0
WA 010 VC	10	25	R 3/8"	32,0
WA 013 VC	13	25	R 1/2"	39,0
WA 020 VC	20	25	R 3/4"	48,0
WA 025 VC	25	25	R 1"	55,0
WA 032 VC	32	25	R 1.1/4"	67,0
WA 040 VC	40	25	R 1.1/2"	74,0
WA 050 VC	50	25	R 2"	90,0

Product versions		
WA VC RG	Connector VC, red bronze, Red bronze	
WA VC VA	Connector VC, VA, Stainless steel	