BETON 40

Concrete supply hose

HANSA-FLEX

Properties

Application	Construction industry
Special features	pricked
Standard	DIN 53516 < 60 mm3
Inner layer	highly abrasion resistant insulating natural rubber
Insert	four highly tear-resistant synthetic textile inserts with copper braids
Outer layer	synthetic rubber with high ozone, abrasion, and weather resistance
Colour	black
Temp. min.	-40 °C
Temp. max.	70 °C
Media	Mortar, concrete, screed



Item

Identification	Inches	Internal Ø (mm)	External Ø (mm)	Operating pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)	Roll length (m)
BETON 40-25-38	1"	25,4	38,0	40,0	120	110	40
BETON 40-32-46	1.1/4"	32,0	46,0	40,0	120	160	40
BETON 40-35-49	1.3/8"	35,0	49,0	40,0	120	175	40
BETON 40-38-54	1.1/2"	38,0	54,0	40,0	120	190	40
BETON 40-50-68	2"	50,8	68,0	40,0	120	280	40
BETON 40-63.5-83.5	2.1/2"	63,5	83,5	40,0	120	375	40

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.