# BETON 40

Concrete supply hose

HANSA-FLEX

## Properties

| | |
|---|---|
| **Application** | Construction industry |
| **Special features** | pricked |
| **Standard** | DIN 53516 < 60 mm3 |
| **Inner layer** | highly abrasion resistant insulating natural rubber |
| **Insert** | four highly tear-resistant synthetic textile inserts with copper braids |
| **Outer layer** | synthetic rubber with high ozone, abrasion, and weather resistance |
| **Colour** | black |
| **Temp. min.** | -40 °C |
| **Temp. max.** | 70 °C |
| **Media** | Mortar, concrete, screed |




## Item

| Identification | Inches | Internal Ø (mm) | External Ø (mm) | Operating pressure (bar) | Burst pressure (bar) | Min. bending radius (mm) | Roll length (m) |
|---|---|---|---|---|---|---|---|
| **BETON 40-25-38** | 1" | 25,4 | 38,0 | 40,0 | 120 | 110 | 40 |
| **BETON 40-32-46** | 1.1/4" | 32,0 | 46,0 | 40,0 | 120 | 160 | 40 |
| **BETON 40-35-49** | 1.3/8" | 35,0 | 49,0 | 40,0 | 120 | 175 | 40 |
| **BETON 40-38-54** | 1.1/2" | 38,0 | 54,0 | 40,0 | 120 | 190 | 40 |
| **BETON 40-50-68** | 2" | 50,8 | 68,0 | 40,0 | 120 | 280 | 40 |
| **BETON 40-63.5-83.5** | 2.1/2" | 63,5 | 83,5 | 40,0 | 120 | 375 | 40 |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*