


# PVC TRANSP ST

Soft PVC hose

**HANSA FLEX**

## Properties

<b>Application</b>	Food industry
<b>Special features</b>	extremely durable, flexible, resistant to pressure and abrasion, UV and weatherproof
<b>Inner layer</b>	PVC suitable for use with foodstuffs
<b>Insert</b>	embedded steel wire helix
<b>Outer layer</b>	PVC suitable for use with foodstuffs
<b>Colour</b>	Transparent
<b>Temp. min.</b>	-5 °C
<b>Temp. max.</b>	60 °C
<b>Media</b>	Fruit juices Mineral water Wines liquid foodstuffs containing up to 15% alcohol



## Item

Identification	Inches	Internal Ø (mm)	External Ø (mm)	Burst pressure (bar)	Vacuum (bar)	Min. bending radius (mm)	Roll length (m)
PVC 10 TRANSP ST	3/8"	10,0	16,0	21	0,90	20	50
PVC 12 TRANSP ST	1/2"	12,0	17,8	21	0,90	25	50
PVC 16 TRANSP ST	5/8"	16,0	21,7	18	0,90	35	50
PVC 19 TRANSP ST	3/4"	20,0	27,1	15	0,90	50	50
PVC 25 TRANSP ST	1"	25,4	33,3	15	0,90	60	50
PVC 32 TRANSP ST	1.1/4"	31,8	40,1	13	0,90	75	50
PVC 38 TRANSP ST	1.1/2"	38,1	46,7	12	0,90	90	50
PVC 51 TRANSP ST	2"	50,8	61,1	9	0,80	125	50
PVC 63 TRANSP ST	2.1/2"	63,0	75,0	7	0,70	150	30
PVC 76 TRANSP ST	3"	76,0	89,9	6	0,70	195	30
PVC 102 TRANSP ST	4"	101,6	116,3	6	0,60	300	30