


Properties

Application	Connection fitting for metal hoses
Connection 1	Pipe sockets
Sealing form 1	Cutting ring connection
Standard	ISO 8434-1
Short code	BEL
Construction	straight
Series	light
Material	Stainless steel 1.4571



Note

Final cutting ring assembly must be carried out in the hardened pre-assembly socket (VOM...).
As an alternative we recommend connector shape AFL or AOL.

Ordering information

Other designs available on request

Item

Identification	DN	PN (bar)	Series	D1 (mm)	s (mm)	L1 (mm)
WA 004 FL VA	4	250	6 L	6	1,0	25
WA 006 FL VA	6	250	8 L	8	1,0	30
WA 008 FL VA	8	240	10 L	10	1,0	30
WA 010 FL VA	10	200	12 L	12	1,0	30
WA 013 FL VA	13	250	15 L	15	1,5	32
WA 016 FL VA	16	160	18 L	18	1,5	32
WA 020 FL VA	20	160	22 L	22	1,5	36
WA 025 FL VA	25	100	28 L	28	2,0	40
WA 032 FL VA	32	100	35 L	35	2,0	45
WA 040 FL VA	40	100	42 L	42	2,0	45

Product versions

WA FL	Connector ... FL, steel, Steel (weldable)
WA FL CU	Connector ... FL, copper, Copper