


# NY 800 NC (R8)

Thermoplastic high pressure hose, electrically nonconductive

**HANSA FLEX**

## Properties

<b>Application</b>	High pressure circuits general application
<b>Special features</b>	high ozone and abrasion resistance very good reverse bending fatigue strength slight volumetric expansion
<b>Standard</b>	SAE J517 - 100 R8 Non Conductive
<b>Inner layer</b>	Polyester elastomer
<b>Insert</b>	one aramide braided insert
<b>Outer layer</b>	Polyurethane
<b>Colour</b>	orange
<b>Temp. min.</b>	-40 °C
<b>Temp. max.</b>	100 °C
<b>Elongation</b>	+ 0 % to - 1 %
<b>Media</b>	Mineral oil Synthetic oils Water-oil emulsions (up to 60°C) Water (0°C to + 60°C)



## Note

Electrical conductivity < 50µA to DIN EN 855

## Item

Identification	DN*	Size	Inches	Internal Ø (mm)	External Ø (mm)	Operating pressure (bar)	Burst pressure (bar)	Min. bending radius (mm)
<b>NY 804 NC</b>	5	3	3/16"	5,0	8,9	350,0	1400	30
<b>NY 806 NC</b>	6	4	1/4"	6,5	11,5	350,0	1400	50
<b>NY 808 NC</b>	8	5	5/16"	8,1	13,4	300,0	1200	55
<b>NY 810 NC</b>	10	6	3/8"	9,7	15,5	280,0	1120	60
<b>NY 813 NC</b>	12	8	1/2"	13,0	19,9	245,0	980	80
<b>NY 820 NC</b>	19	12	3/4"	19,5	26,9	165,0	660	150
<b>NY 825 NC</b>	25	16	1"	25,9	34,2	140,0	560	200

DN = Nominal diameter, nominal width