
# HK DTDA

2/2-way solenoid-operated directional control valve DTDA

## Properties

| | |
|---|---|
| **Design** | direct-controlled<br>with manual emergency operation |
| **Scope of supply** | without coil or plug |
| **Operating pressure** | max. 350 bar |






## Description

Max. leakage 0.7cm3/min at 250 bar and 32cSt

## Ordering information

Please order solenoid coil separately (see accessories)

## Item

| Identification | Volumetric flow min. (L/min) | A (mm) | B (mm) | C (mm) | Screw-in housing | Screw-in thread | AF (mm) | Tightening torque (N-m) | Design | Weight (kg) |
|---|---|---|---|---|---|---|---|---|---|---|
| **HK DTDA MCN** | 40,0 | 89,0 | 35,0 | 37,0 | HK GAU / HK GAUS / HK GAV | T-13A | 22 | 48,0 | power-off closed, double locking | 0,5 |
| **HK DTDA MHN** | 40,0 | 89,0 | 35,0 | 37,0 | HK GAU / HK GAUS / HK GAV | T-13A | 22 | 48,0 | power-off open, double locking | 0,5 |

## Accessories

| | |
|---|---|
| **HK SP 770** | Coil for cartridge valve SUN |
| **HK GEH GA** | Valve housing for cartridge valve T-13A |
| **HK GEH GBA** | Housing sandwich plate with measurement connctn. for cart. valve T-13A |
| **HK GEH GBY** | Housing sandwich plate with measurement connctn. for cart. valve T-13A |
| **HK GEH MBJ** | Housing sandwich plate for cartridge valve T-31A |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*