


Properties	
Design	direct-controlled
Operating pressure	max. 350 bar





## Note

These valves must be set according to the application.

## Description

Only adjustable when pressure at port 1 < 50 bar connection 2 can be loaded with max. pressure Response time approx. 2 ms

Response time approx. 2 ms
Item

Item										
Identification	Setting range min.	Setting range max.	Qmax	Α	В	Screw-in housing	Screw-in thread	AF	Tightening torque	Weight
	(bar)	(bar)	(L/min)	(mm)	(mm)			(mm)	(N-m)	(kg)
HK RD DA LAN	35	210	95	61,0	40,0	HK FAU / HK FAUS	T-10A	22	50,0	0,5
HK RD DA LWN	55	315	95	61,0	40,0	HK FAU / HK FAUS	T-10A	22	50,0	0,5
HK RD FA LAN	35	210	200	64,0	48,0	HK CAV / HK CAVS / HK CAW / HK CAWS	T-3A	28	65,0	0,5
HK RD FA LWN	55	315	200	64,0	48,0	HK CAV / HK CAVS / HK CAW / HK CAWS	T-3A	28	65,0	0,5

Accessories					
HK GEH CA	Valve housing for cartridge valve T-3A				
HK GEH FA	Valve housing for cartridge valve T-10A				
HK HR SUN	Hand wheel for cartridge valve SUN				