



Note

Tolerances:

longitudinal dimension according to DIN 7715 - Part 5 P2,

thickness according to DIN 7715 - Part 5 P3,

Item

Identification	D (mm)	d (mm)	s (mm)
BOERD DI DN15 PN16	50,0	22,00	2,0
BOERD DI DN20 PN16	60,0	28,00	2,0
BOERD DI DN25 PN16	70,0	35,00	2,0
BOERD DI DN32 PN16	82,0	43,00	2,0
BOERD DI DN40 PN16	92,0	49,00	2,0
BOERD DI DN50 PN16	107,0	61,00	2,0
BOERD DI DN65 PN16	127,0	77,00	2,0
BOERD DI DN100 PN16	162,0	115,00	2,0
BOERD DI DN125 PN16	192,0	141,00	2,0
BOERD DI DN150 PN16	218,0	169,00	2,0
BOERD DI DN175 PN10	248,0	195,00	2,0
BOERD DI DN200 PN16	273,0	220,00	2,0
BOERD DI DN250 PN16	330,0	274,00	2,0
BOERD DI DN300 PN16	385,0	325,00	2,0
BOERD DI DN350 PN16	445,0	368,00	2,0
BOERD DI DN400 PN16	497,0	420,00	2,0
BOERD DI DN450 PN16	557,0	470,00	2,0