


Properties			
Design	Wipers		
Sliding speed max.	0,5 m/s		
Temp. min.	-20 °C		
Temp. max.	200 °C		
Media	Mineral oils Water emulsions		
Installation	is pressed into an open groove		
Material	(1) Sleeve: Steel Wiper: FPM		
Application	Hydraulics		



Toleranz / Tolerance				
d	D	L		
h11	Н8	+0,20		



Description

Low spatial requirement.

No penetration of dirt via the outer metal ring.

Simple solution.

Ordering information

For special operating conditions (fluid, temperature, pressure ...) please contact us.

Item					
Identification	d (mm)	D (mm)	L (mm)	H (mm)	
GA 16 22-3 FPM	16	22	3,0	4	
GA 25 35-7 FPM	25	35	7,0	10	
GA 30 40-7 FPM	30	40	7,0	10	
GA 32 45-4 FPM	32	45	4,0	8	
GA 45 55-7 FPM	45	55	7,0	10	
GA 45 60-7 FPM	45	60	7,0	10	
GA 50 56-5 FPM	50	56	5,0	8	
GA 60 70-7 FPM	60	70	7,0	10	
GA 63 75-7 FPM	63	75	7,0	10	
GA 70 80-7 FPM	70	80	7,0	10	