


## Properties

<b>Design</b>	Wipers
<b>Sliding speed max.</b>	0,5 m/s
<b>Temp. min.</b>	-20 °C
<b>Temp. max.</b>	200 °C
<b>Media</b>	Mineral oils Water emulsions
<b>Installation</b>	is pressed into an open groove
<b>Material</b>	(1) Sleeve: Steel Wiper: FPM
<b>Application</b>	Hydraulics



Toleranz / Tolerance		
d	D	L
h11	H8	+0,20 0



## Description

Low spatial requirement.  
No penetration of dirt via the outer metal ring.  
Simple solution.

## Ordering information

For special operating conditions (fluid, temperature, pressure ...) please contact us.

## Item

Identification	d (mm)	D (mm)	L (mm)	H (mm)
GA 16 22-3 FPM	16	22	3,0	4
GA 25 35-7 FPM	25	35	7,0	10
GA 30 40-7 FPM	30	40	7,0	10
GA 32 45-4 FPM	32	45	4,0	8
GA 45 55-7 FPM	45	55	7,0	10
GA 45 60-7 FPM	45	60	7,0	10
GA 50 56-5 FPM	50	56	5,0	8
GA 60 70-7 FPM	60	70	7,0	10
GA 63 75-7 FPM	63	75	7,0	10
GA 70 80-7 FPM	70	80	7,0	10